



- Beam type chassis incorporating dual tow heights
- 1.35m 9 leaf overslung mechanical suspension;
- K-Hitch parallel bearing enclosed cam drum brake axles, spider or 10 stud hubs
- ROH silver steel rims in spider or 10 stud
- Bridgestone 11R 22.5 R187 tyres
- 60mm low profile ball race
- Jost JSK 38 3.5" adjustable turntable
- A-frame length to suit application with 314kn 50mm tow eye
- Abrasive blasted to class 2.0, epoxy primed and two pack topcoated
- Hella LED lights to ADR standard with independent earth circuits using soldered and heat-shrink tubing protected joints
- ABK brake kit to ADR 38 standard with yard release valve
- Moulded and reinforced rubber mudflaps front and rear
- Reinforced vinyl roll up mudguards
- Bolt-on mud guard assemblies for ease of maintenance
- **Tare weight: 2.5t**

**Choose from our wide range of optional extras
—or discuss a customised solution with us.**

- Air bag suspension with extra tank, dump facility and pressure gauges to suit application
- Disc brakes
- Unitized wheel bearings (1,000,000 km warranty)
- Alcoa or Speedline aluminium 10 stud wheels
- Tyres: different patterns and either 255/70 22.5" or 265/70 19.5" sizing
- Hydraulic line to A-frame
- Spray suppressant skirting
- On-board weighing systems
- **Tare weights: 2.0t to 2.5t**



TRI AXLE DOLLY



STANDARD FEATURES

- 2.4m 8 leaf under-slung mechanical suspension;
- K-Hitch parallel bearing, enclosed cam drum brake axles, spider or 10 stud hubs
- ROH silver steel rims in spider or 10 stud
- Bridgestone 11R 22.5 R187 tyres
- 60mm low profile ball race
- Jost JSK 38 3.5" adjustable turntable
- A-frame length to suit application with 314kn 50mm tow eye
- Abrasive blasted to class 2.0, epoxy primed and two pack topcoated
- Hella LED lights to ADR standard with independent earth circuits using soldered and heat-shrink tubing protected joints
- ABK brake kit to ADR 38 standard with yard release valve
- Moulded and reinforced rubber mudflaps front and rear
- Reinforced vinyl roll up mudguards
- Bolt-on mudguard assemblies for ease of maintenance
- **Tare weight: 3.8t**



OPTIONAL FEATURES

**Choose from our wide range of optional extras
—or discuss a customised solution with us.**

- Air bag suspension with extra tank, dump facility and pressure gauges to suit application
- Mechanical suspension with 3 leaf parabolic springs
- Disc brakes
- Unitized wheel bearings (1,000,000 km warranty)
- Alcoa or Speedline aluminium 10 stud wheels
- Tyres: different patterns and either 255/70 22.5" or 265/70 19.5" sizing
- Hydraulic line to A-frame
- Spray suppressant skirting
- On-board weighing systems
- **Tare weights: 3.0t to 3.8t**



Bruce Rock
ENGINEERING

Tel: **(08) 9061 1253**

Fax: (08) 9061 1188

15 Swan Street, Bruce Rock WA 6418

Email: brucerockengineering@westnet.com.au

Web: www.bruckerockengineering.com.au

ABN: 79 447 876 298