

GRAIN TIPPERS



STANDARD FEATURES

- 2.4 m 8-leaf overslung mechanical suspension
- K-Hitch parallel bearing enclosed cam drum brake axles, spider or 10 stud hubs
- ABK brake kit to ADR 38/02 standard with yard release valve
- ROH silver steel rims in spider or 10 stud
- Bridgestone 11R 22.5 R187 tyres
- Bolt-in king pins with bolt-in ball race block
- 2 speed landing legs
- Dual spare tyre carrier with one spare tyre and rim
- Abrasive blasted to class 2.0, epoxy primed and two pack topcoated
- Internal body painted with a self-priming, glass-reinforced, high-build epoxy mastic
- 9.1 x 1.8m 3.0 mm high tensile body (42m³)
- Body is fully rubber mounted, by individual vulcanised rubber pads
- Body formed with no sheet overlaps and with fully welded seams (no hidden rust traps)
- Full bowl shape with all corners chamfered that eliminates stick-up, ensuring the product runs out with ease and minimising sweep out and contamination
- Hella LED lights to ADR standard, with independent earth circuits using soldered and heat-shrink tubing protected joints
- Side swing tailgate with stainless steel centre door and safety chains
- Manual bottom tailgate locks with stainless steel side safety locks
- Reinforced roll tarp with fully adjustable handle
- Hyva 50t hoists
- Road train hitch plate with air, electrical and hydraulic couplings
- Manual hydraulic diverter
- Moulded and reinforced rubber mudflaps front and rear
- Reinforced vinyl roll-up mudguards
- Bolt-on mud guard assemblies for ease of maintenance
- Hidden shovel rack
- Steps: full width at front, internal front and rear, external front, rear and side
- Tare weight: 7.15t





OPTIONAL FEATURES

Choose from our wide range of optional extras
—or discuss a customised solution with us.

- Various body lengths and heights to suit application and cubic metre capacity requirements
- Air bag suspension with extra tank, dump facility and pressure gauges to suit application
- Mechanical suspension with three leaf parabolic springs
- Disc brakes
- Unitized wheel bearings (1,000,000 km warranty)
- Alcoa or Speedline aluminium 10 stud wheels
- Tyres: different patterns and either 255/70 22.5" or 265/70 19.5" sizing
- Clear two pack over topcoat and/or stripes
- Air operated tailgate
- Air operated diverter
- Spray suppressant skirting
- On-board vehicle weighing systems
- **Tare weights: 6.2t to 7.2t**

GENERAL PURPOSE TIPPERS



- 8.5m x 1.2m standard body size
- All the chassis and running gear options of the grain tippers
- Optional heights and lengths to suit individual cubic metre capacity requirements
- Floor and wall combinations of 5.0mm and 3.2mm hardox and/or high tensile
- Heavy duty, side swing tailgates with air operated lock
- Roll tarp or concertina tarp
- **Tare weights: 6.2t to 7.2t**



Bruce Rock
ENGINEERING

Tel: **(08) 9061 1253**

Fax: (08) 9061 1188

15 Swan Street, Bruce Rock WA 6418

Email: brucerockengineering@westnet.com.au

Web: www.bruckerockengineering.com.au

ABN: 79 447 876 298